

TELEtek

MULTISWITCH / 17 Input Multiswitch

TS-1716

- Active terrestrial
- Compact design
- DiSEqC 2.0 compatible
- External SMPS power supply
- Quad LNB compatibility is available upon request



| Model | | TS-1708 | TS-1712 | TS-1716 | TS-1720 | TS-1724 | TS-1732 | TS-1752 |
|-------------------------------|--------------------------|------------|------------|-------------------------------------|------------|---------|------------|------------|
| Inputs | SAT polarities + Terr | 16 + 1 | 16 + 1 | 16 + 1 | 16 + 1 | 16 + 1 | 16 + 1 | 16 + 1 |
| Taps | | 8 | 12 | 16 | 20 | 24 | 32 | 50 |
| Tap loss | SAT 950...2150 MHz | -1...+2 | -2...+1 | | -2...0 | | -2...-1 | -8...-5 |
| | active Terr 47...862 MHz | -1...+1 | -1...+1 | | -1...0 | | -2...-1 | -14...-5 |
| | passive Terr 5...862 MHz | -21...-19 | -21...-19 | | -21...-20 | | -22...-21 | -34...-25 |
| Return loss | SAT 950...2150 MHz | | | | >10 | | | |
| | Terr 5...862 MHz | | | | >10 | | | |
| Isolation | SAT to Terr | | | | >30 | | | |
| | Terr to SAT | | | | >24 | | | |
| | Cross polar. H/V | | | | >35 | | | |
| Output level | SAT (IMD3, EN50083-5) | | | | 100 | | | |
| | Terr (IMD3, EN50083-5) | 99 | 96 | | | 95 | | 94 |
| LNB power supply | | | | 13 VDC / 4000 mA | | | | |
| Consumption from the receiver | | | | 50 | | | | |
| Switching commands | | | | DiSEqC2.0 - 13V/18V , 0/22 KHz,Tone | | | | |
| Dimensions | LxWxH mm | 120x310x40 | 190x310x40 | | 260x310x40 | | 310x310x40 | 525x310x40 |

Teletek Elektronik San.ve Tic. A.S.
 Merkez Mah. Ayazma Cad. No.55/2
 34406 Kagithane-Istanbul TURKEY
 Phone +90 212 295 9700
 Fax +90 212 295 4243
 E-Mail teletek@teletek.com.tr