

TELEtek

MULTISWITCH / 9 Input Multiswitch

MS-920

- Excellent signal quality even at low signals, by the patented transistor switching design
- Active/passive Terrestrial switch
- Compact design
- DiSEqC 2.0 compatible
- External SMPS power supply
- Quad LNB compatibility is available upon request



Model		MS-904	MS-908	MS-912	MS-916	MS-920	MS-924	MS-932
Inputs	SAT polarities + Terr	8 + 1	8 + 1	8 + 1	8 + 1	8 + 1	8 + 1	8 + 1
Taps		4	8	12	16	20	24	32
Tap loss	SAT 950...2150 MHz	0...+4		-1...+3		-2...+2		-2...+1
	active Terr 47...862 MHz	+1...+5		-1...+3		-2...+2		-4...+1
	passive Terr 5...862 MHz	-19...-15		-21...-17		-22...-18		-24...-19
Return loss	SAT 950...2150 MHz							>10
	Terr 5...862 MHz							>10
Isolation	SAT to Terr							>60
	Terr to SAT							>24
	Cross polar. H/V							>30
Output level	SAT (IMD3,EN50083-5)							100
	Terr (IMD3,EN50083-5)	92		92		92		
LNB power supply				13 VDC / 1500 mA				
Consumption from the receiver	mA			40				
Switching commands				DiSEqC 2.0 -13V/18V, 0/22 KHz,Tone				
Dimensions	LxWxH mm	110x190x40		170x190x40		230x190x40		300x190x40

Teletek Elektronik San.ve Tic. A.S.
 Merkez Mah. Ayazma Cad. No.55/2
 34406 Kagithane-Istanbul TURKEY
 Phone +90 212 295 9700
 Fax +90 212 295 4243
 E-Mail teletek@teletek.com.tr