

TELEtek

MULTISWITCH / 5 Input Multiswitch

TS-524

- Excellent signal quality even at low signals, by the patented transistor switching design
- Active/passive Terrestrial switch
- Compact design
- DiSEqC 2.0 compatible
- External SMPS power supply
- Quad LNB compatibility is available upon request



Model		TS-504	TS-508	TS-512	TS-516	TS-520	TS-524	TS-532	
Inputs	SAT polarities + Terr	4 + 1	4 + 1	4 + 1	4 + 1	4 + 1	4 + 1	4 + 1	
Taps		4	8	12	16	20	24	32	
Tap loss	SAT 950...2150 MHz		-2...+2		-3...+1		-4...0		-4...-1
	active Terr 47...862 MHz	dB	1...+5	-1...+3	-2...+2		-4...+1		-5...+1
	passive Terr 5...862 MHz		-19...-15	-21...-17	-22...-18		-24...-19		-25...-19
Return loss	SAT 950...2150 MHz	dB			>10				
	Terr 5...862 MHz				>10				
Isolation	SAT to Terr	dB			>60				
	Terr to SAT				>24				
	Cross polar. H/V				>30				
Output level	SAT (IMD3,EN50083-5)	dBμV			100				
	Terr (IMD3,EN50083-5)		92		92		92		
LNB power supply					13 VDC / 1500 mA				
Consumption from the receiver	mA				40				
Switching commands					DiSEqC 2.0 -13V/18V, 0/22 KHz,Tone				
Dimensions	LxWxH mm	110x130x40		170x130x40		230x130x40		300x130x40	

Teletek Elektronik San.ve Tic. A.S.
 Merkez Mah. Ayazma Cad. No.55/2
 34406 Kagithane-Istanbul TURKEY
 Phone +90 212 295 9700
 Fax +90 212 295 4243
 E-Mail teletek@teletek.com.tr