



EKSELANS BY ITS

## TAPS WITH F CONNECTOR DF 2XX / DF 14XX / DF 18XX

Screening factor A class

DC pass in trunk line

5-2400 MHz

REFERENCE		DF 212	DF 216	DF 220	DF 224	DF 412	DF 416	DF 420	DF 424	DF 816	DF 820	DF 824
Code		142001	142002	142003	142004	142005	142006	142007	142008	142009	142010	142011
Passband	<b>MHz</b>	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400	5-2400
Outputs	<b>N°</b>	2	2	2	2	4	4	4	4	8	8	8
Tap loss	<b>dB (+/-1)</b>	12	16	20	24	12	16	20	24	16	20	24
Insertion loss	<b>dB 860 MHz</b>	<2,2	<1,6	<1,1	<1	<3,2	<1,8	<1,5	<1,3	<3,8	<1,9	<1,4
	<b>dB 2400 MHz</b>	<3,5	<2,6	<2,6	<2,3	<4,5	<3,5	<2,1	<2	<4,9	<3,2	<2,1
Outputs isolation	<b>dB</b>	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20	>20
Return loss	<b>dB</b>	>10	>10	>10	>10	>10	>10	>10	>10	>10	>10	>10
DC Pass	<b>mA</b>	500	500	500	500	500	500	500	500	500	500	500



DF 2XX



DF 4XX



DF 8XX