



Insertion loss (in-out) 5-40 Mhz	< 8.5 dB
Insertion loss (in-out) 860-1000 MHz	< 10.5 dB
ISOLATION	
Isolation (tap-tap) 40-470 MHz	> 28.0 dB
Isolation (tap-tap) 470-860 MHz	> 24.0 dB
Isolation (tap-tap) 5-40 MHz	> 26.0 dB
Isolation (tap-tap) 860-1000 MHz	> 24.0 dB
RETURN LOSS	
Return loss (in-out) 40-470 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 470-860 MHz	> 20.0 / > 20.0 dB
Return loss (in-out) 5-40 MHz	> 22.0 / > 20.0 dB
Return loss (in-out) 860-1000 MHz	> 20.0 / > 20.0 dB
ELECTRICAL	
Impedance	75 $\Omega$
OPERATIONAL	
Certification	CE
DC Passthrough	Yes
CONNECTORS	
Connector Type	F-female
Number of outputs	6
MECHANICAL	
Product Depth	16 mm
Packaging Depth	0,120 m
Packaging Height	0,020 m
Total Weight	0,051 kg
Packaging Width	0,050 m
Net Weight	0,045 kg

Packing QTY	1
Tara Weight	0,006 kg
Weight (kg)	0 kg
Product Width	117 mm
Product Height	60 mm

---