

TELEtek

MULTISWITCH / 5 Input Multiswitch

TK-516

- Excellent signal quality even at low signals, by the patented transistor switching design
- Active/passive Terrestrial switch
- Compact design
- DiSEqC 2.0 compatible
- External SMPS power supply



Model		TK-504	TK-508	TK-512	TK-516	TK-520	TK-524	TK-532
Inputs	SAT polarities + Terr	4 + 1	4 + 1	4 + 1	4 + 1	4 + 1	4 + 1	4 + 1
Taps		4	8	12	16	20	24	32
Trunk loss	SAT 950...2150 MHz	-1...-2			-2...-3		-2...-4	-2...-5
	Terr 5...862 MHz	-3...-4				-4...-5		
Tap loss	SAT 950...2150 MHz	-2...+2			-3...+1		-4...0	-4...-1
	active Terr 47...862 MHz	-2...+2	-4...0		-5...-1		-7...-2	-8...-2
	passive Terr 5...862 MHz	-22...-18	-24...-20		-25...-21		-27...-22	-28...-22
Return loss	SAT 950...2150 MHz				>10			
	Terr 5...862 MHz				>10			
Isolation	SAT to Terr				>60			
	Terr to SAT				>24			
	Cross polar. H/V				>30			
Output level	SAT (IMD3, EN50083-5)				100			
	Terr (IMD3, EN50083-5)				92			
LNB power supply				13 VDC / 1500 mA				
Consumption from the receiver				40				
Switching commands				DiSEqC 2.0 -13V/18V , 0/22 KHz,Tone				
Dimensions	LxWxH mm	110x130x40		170x130x40		230x130x40		300x130x40

Teletek Elektronik San.ve Tic. A.S.
 Merkez Mah. Ayazma Cad. No.55/2
 34406 Kagithane-Istanbul TURKEY
 Phone +90 212 295 9700
 Fax +90 212 295 4243
 E-Mail teletek@teletek.com.tr