

Ek

EKSELANS BY ITS

# SPLITTERS



## RQC 2M

- ✓ QuiCoax connection system
- ✓ 2 Outputs
- ✓ Low insertion loss
- ✓ DC pass
- ✓ MINI format



RQC 2M

01



Reduce to minimum  
**installation time**

02



**No need**  
of tools

03



Guarantees  
an **excellent**  
**connected** and  
minimizes the  
**space**

04



Very high  
**shielding factor**  
**CLASS A +10dB**  
throughout the  
band

05



Eliminate the use  
of **connectors**  
and **associated**  
**costs**

06



**QuiCoax,**  
the new  
**Standard of**  
**Connection**



## TECHNICAL TABLE

REFERENCE	RQC 2M
CODE	141009
LOSS	
Insertion loss (IN-OUT) 5-47 MHz	<3.5 dB
Insertion loss (IN-OUT) 47-950 Mhz	<4.0 dB
Insertion loss (IN-OUT) 950-2150 MHz	<5.5 dB
Insertion loss (IN-OUT) 2150-2400 Mhz	<6.0 dB
ISOLATION	
Isolation (OUT-OUT) 5-47 MHz	>35 dB
Isolation (OUT-OUT) 47-950 MHz	>30 dB
Isolation (OUT-OUT) 950-2150 MHz	>22 dB
Isolation (OUT-OUT) 2150-2400 MHz	>20 dB
RETURN LOSS	
Return loss 5-47 MHz	>15 dB
Return loss 47-950 MHz	>15 dB
Return loss 950-2150 MHz	>15 dB
Return loss 2150-2400 MHz	>12 dB
OPERATIONAL	
Impedance	75 $\Omega$
Application	SAT, MATV 2.4Ghz +DC
Screening Efficiency	EN50083-2 Class A +10dB
DC Passthrough	Yes (max. 500mA)
Environment	Indoor
CONEXIÓN DEL CABLE	
Numero de entradas	1
Número de salidas	2
Tipo de conexión	QuiCoax
MECHANICAL	
Product Depth	16 mm
Product Height	38 mm
Product Width	75 mm
Packing QTY	1
Net Weight	0,081kg

## Screening

100.0 kHz - 3.0 GHz Test length: 1.00m

