

TELEtek

MULTISWITCH / 13 Input Multiswitch

TS-1320

- Active terrestrial
- Compact design
- DiSEqC 2.0 compatible
- External SMPS power supply
- Quad LNB compatibility is available upon request



Model		TS-1308	TS-1312	TS-1316	TS-1320	TS-1324	TS-1332	TS-1350
Inputs	SAT polarities + Terr	12 + 1	12 + 1	12 + 1	12 + 1	12 + 1	12 + 1	12 + 1
Taps		8	12	16	20	24	32	50
Tap loss	SAT 950...2150 MHz	-1...+2		-2...+1		-2...0	-2...-1	-8...-5
	active Terr 47...862 MHz	-1...+1		-1...+1		-1...0	-2...-1	-14...-5
	passive Terr 5...862 MHz	-21...-19		-21...-19		-19...-20	-22...-21	-34...-25
Return loss	SAT 950...2150 MHz				>10			
	Terr 5...862 MHz				>10			
Isolation	SAT to Terr				>30			
	Terr to SAT				>24			
	Cross polar. H/V				>35			
Output level	SAT (IMD3, EN50083-5)				100			
	Terr (IMD3, EN50083-5)				92			
LNB power supply				13 VDC / 4000 mA				
Consumption from the receiver	mA			50				
Switching commands				DisEqC2.0 - 13V/18V, 0/22 KHz,Tone				
Dimensions	LxWxH mm	120x310x40	190x310x40		260x310x40		310x310x40	525x310x40

Teletek Elektronik San.ve Tic. A.S.
 Merkez Mah. Ayazma Cad. No.55/2
 34406 Kagithane-Istanbul TURKEY
 Phone +90 212 295 9700
 Fax +90 212 295 4243
 E-Mail teletek@teletek.com.tr